


### Mobile Lab



## Instruction Manual

### Summary and Breakthrough

The invention of this mini **RED-OXY LAB** is to conduct a laboratory-scale investigation of the effectiveness of **RED-OXY** to eliminate (<u>see list of contaminants</u>) from any water or wastewater and to optimize the process with respect to efficiency, cost and implementation. **RED-OXY LAB** summarizes the breakthrough experiments which can be carried out in the laboratory in your company or directly at the field. The final results of the contaminated water from any source can be discussed with your customer on the spot.




### Article No Description Qty 399001006 RED-OXY LAB Box (40 L) 1 112472190 2 Filter head glass body 2 005800018 Filter plate with flow restrictor 005269437 Filter head Gaskets (O-Ring 83) 2 005269436 Filter head Gaskets (O-Ring 86) 2 112922190 Filter Head PP Funnel 2 ASA60N23603 **Connection Adapter** 2 6237708 2 Filter Flask (1000 ml) 0173076327 Plastic Mug (1000 ml) 1 0173076319 Dilution Bottles (250 ml, with Cap) З 11001002 Plastic Syringes (50 ml) 6 3209150019 Plastic Spoon (10 ml) З 0179251602 Funnel З 3209049426 Sludge Removal Filter 10 0173076317 KL-Sample Bottle (with Cap) 1 0173076317 CC-Sample Bottle (with Cap) 1 010030009 Katalox-Light 1 liter bag 2 010001001 Catalytic Carbon 1 liter Bag 2 0030010190 RED<sup>×</sup> Granule (500 g) 1 0030010200 OXY<sup>x</sup> Granule (500 g) 1 0030010210 ADSORB<sup>x</sup> Granule (500 g) 1

**RED-OXY** Mobile Lab consists of the followings


page

### www.watchwater.de






 Assemble The Filter head to fit on the Filter Flask with the help of the Adapter. Prepare two sets one for Katalox-Light and one for Catalytic Carbon.



2. Put Katalox-Light and Catalytic Carbon from the respective 1 liter bag and pour the media in two filter set up

page



3. Pour one liter of clean water (with the mug) through both KL and CC media. Fines might be observed. Throw away the water collected in the filter flasks.



 Prepare the dosing solution from the respective chemical diluting them in the water. Dilution strength is contaminants dependent. See **RED-OXY Part I** for more information.

www.watchwater.de



## Instruction of Use


Water Technology & Chemicals

page


- 5 Loading the chemicals for injecting
- 6 Inject chemicals in the raw water



5. Load the prepared solution in the provided syringes. Make sure to use separate syringes for each chemical. The loading amount should be noted to realize the performance.




 Put 1 liter of test water in the plastic mug and inject RED & OXY simultaneously with both hands. Stir the mixture for 1 minute. Add ADSORB to the mixture and stir for 1 minute. Leave the solution in rest for 10 minutes.



www.watchwater.de

# RED-OXY Mobile LAB

Water Technology & Chemicals



If the appearance or results are not satisfactory one might need to adjust the chemical concentrations and repeat the test.

page

Our recommendations:

- The unused (if remains) diluted solution can be stored in the provided bottles.
- All the equipments must be thoroughly washed and clean
- It's best recommended to use a new packet of filter media (Katalox-Light and Catalytic Carbon) for each test.
- Used filter media is not recommended for re-use. It might affect the performance
- All the instructions are important and should be followed accordingly.
- Contact us when you may need spare parts, chemicals or filter media for your mobile lab. Please refer to the article numbers from the front page.

Distributed by:	Manufact	ured by:
	WATCH WATER WATCH WATER WATCH Campany	
Address:	Address:	Fahrlachstraße 14 Mannheim, D-68165, Germany
Tel:	Tel:	+49 621 87951-0
Fax:	Fax:	+49 621 87951-99
Email:	Email:	info@watchwater.de